

# **MATERIAL SAFETY DATA SHEET**

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product Name: Plascon Floor Paint (FPT Range)

Company Name: Kansai Plascon (Pty) Ltd

Address: P.O. Box 4010 Luipaardsvlei

1743

 Telephone:
 (011) 951 4500

 Facsimile:
 (011) 955 2841

 Contact Person:
 Mr.C.Costa

#### **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical Class:** Emulsion based paint **Classification:** Not classified as hazardous

R Phrases: None S Phrases: S2, S24/25

No significant quantity of other classified hazardous substances present.

# **SECTION 3. HAZARDS IDENTIFICATION**

SAPMA Health Rating: 4-MINIMAL - No great risk to health

**Inhalation:** Can be irritating

**Skin:** Direct contact best to be avoided.

Eyes: Can cause damage Ingestion: Irritating and nauseating

No carcinogenic, mutagenic or genetic effects established.

Medium to long term environmental effects. Contain, monitor & remove.

## **SECTION 4. FIRST AID MEASURES**

**Inhalation:** Move to fresh air. In case of discomfort seek medical attention.

Skin: Wash with soap and water or a recognised skin cleaner. Avoid use of solvents.
 Eyes: Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
 Ingestion: Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical attention.

#### **SECTION 5. FIRE FIGHTING MEASURES**

Product is non-flammable.

No direct explosion hazard expected.

Use foam, CO<sub>2</sub>, dry powder.

## SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect spillage with non-combustible absorbent material and dispose of according to local regulations. Do not allow product to enter drains and sewers

# **SECTION 7. HANDLING AND STORAGE**

Inert substance with no special requirements for hazard containment Store in containers in a well-ventilated environment Store away from direct sun, heat and severe cold





# **MATERIAL SAFETY DATA SHEET**

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

NAME	CAS	OEL (mg/m³)	OEL (ppm)	STOEL (mg/m³)	STOEL (ppm)
XYLENE	1330-20-7	435	100	650	150 RL+S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SAPMA Rating: 4-H-C PPE - Eye protection

Inhalation: In case of insufficient ventilation, use suitable respiratory protection.
 Skin: Avoid contact as far as possible. Wash immediately after contact.
 Eyes: Avoid direct contact. Never touch eyes with dirty hands or gloves.
 Ingestion: Observe the rules of hygiene. Wash before eating, drinking or smoking.



#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Viscous opaque liquid

Flash Point: N/A

Density: 1.310 (typical)
Solubility: Water miscible

#### **SECTION 10. STABILITY AND REACTIVITY**

Stable under normal conditions. Inert - no reaction with fire fighting water

# **SECTION 11. TOXICOLOGICAL INFORMATION**

No carcinogenic, mutagenic or genetic effects established

### **SECTION 12. ECOLOGICAL INFORMATION**

Medium to long term environmental effects. Contain, monitor & remove.

#### **SECTION 13. DISPOSAL INFORMATION**

Can be eliminated from sewerage/effluent by chemical flocculation.

## **SECTION 14. TRANSPORT INFORMATION**

SIN/UN Number: Not classified as dangerous for transport

Shipping Name: Not classified Packaging Group: Not classified Class: Not classified

## **SECTION 15. REGULATORY INFORMATION**

Classification: Not classified as hazardous

S2 Keep out of reach of children (Retail Sales only)

S24/25 Avoid contact with skin and eyes

## **SECTION 16. OTHER INFORMATION**

Take precautionary measures against static discharges. In case of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.